

GOLD APOLLO

WIRELESS PAGING SOLUTION

RESTAURANT TOTAL SOLUTION

ALL-IN-ONE SYSTEM

TABLE CALL SYSTEM

KITCHEN CALL SYSTEM

TWO WAY PAGING SOLUTION

RELAY CONTROL SOLUTION

MATERIAL PICKING SOLUTION

PAGING SYSTEM OVER PBX

WIRELESS CARING SOLUTION



**Tone Only Pager
A07 TCP + AL-A07**

- For guest paging, 430~470MHz
- Transmitter, Charger and Programmer
- Pager is Waterproof and Dustproof IP67
- Supports 60 pagers by extended charger
- Combined with Staff Call pager



AL-A02

- 135~174, 430~470MHz
- IP67
- Rechargeable
- 5.6(L)x21(W)x2(H)cm



**Tone Only Pager
AL-A05**

- 135~174, 430~470MHz
- Rechargeable
- 11(D)x1.5(H)cm



AL-A06

- 135~174, 430~470MHz
- IP67
- OTA function
- 11(D)x1.6(H)cm



**Staff Call
E-Pager**

- 135~174, 430~470MHz
- 4(L)x6(W)x3(H)cm



**Staff Call
AL-A03**

- 135~174, 430~470MHz
- IP53
- Desk Charger
- 5(L)x3(W)x7.4(H)cm



**Numeric Pager
AL-A01**

- 135~174, 430~470MHz
- 10 Canned Messages
- 16 Memory Slots
- 5(L)x3(W)x7.4(H)cm



**Numeric Pager
AL-901**

- 135~174, 430~470MHz
- 10 Canned Messages
- Mini size



AL-924

- 3 navigation buttons
- 135~174, 430~470MHz
- 84 alphanumeric
- Mini size



**Alphanumeric Pager
AL-A25**

- 4 navigation buttons
- 135~174, 430~470MHz
- 84 alphanumeric
- Pocket size



**Alphanumeric Pager
AL-A26**

- 6 navigation buttons
- 135~174, 430~470MHz
- 84 alphanumeric
- 8 capcodes for POCSAG



AL-A27

- 4 navigation buttons
- Larger display
- Desk Charger
- IP54



**Alphanumeric Pager (with charger)
AL-A28**

- 6 navigation buttons
- 135~174, 430~470MHz
- Desk Charger
- IP54



AL-A29

- 6 navigation buttons
- Strong construction
- Desk Charger
- IP67



AL-125

- Two Way (AL-125TR)
- 135~174, 430~470
- Desk Charger
- 8(L) x 5.4(W) x 2(H)cm



**GSM Pager
AL-A30G**

- 7 navigation buttons
- IP67
- Desk Charger
- 8(L)x7(W)x24.5(H)cm



**Table Pager
TP-160**

- 6 navigation buttons
- Relay output
- External Antenna
- 18(L)x11(W)x99(H)cm



**Voice Display
LDN3**

- 3 or 6 digits number display with voice
- Customized recording for any languages
- Up 5 levels volume
- 39(L)x17(W)x52(H) cm



AS-112

- 135~174, 430~470, 929~932 MHz
- 10 Characters per line
- One Line / Two Line switchable
- Priority Message or priority capcode trigger relay output (Model: AS112R)
- 71(L)x16(H)x7(D) cm



LED Display

AS-122

- 135~174, 430~470, 929~932 MHz
- 20 Characters per line
- One Line / Two Line switchable
- Priority Message or priority capcode trigger relay output (Model: AS122R)
- 131(L)x16(H)x7(D) cm



**POCSAG Transmitter
TE-505 Series**

- TE-505 NA : For Tone only pager application
- TE-505 RA : For Alpha pager application, hold up to 30 alpha canned message
- TE-505 RN : For Numeric pager application, 20 digit numeric message
- Up to 100 capcodes
- Data output function via USB



**Alphanumeric Transmitter
TE-510 Series**

- Backlit super twist LCD screen, 4 Lines, Total 84 Alphanumeric on display
- Support Protocol : COMP1, COMP2, SCOPE, GACOMP2, TAPFast travel data entry keypad (PS2 keyboard input option)
- Available to connect with PABX (Model : TE510AD, ADV)
- Available to connect with Voice (Model : TE510ADV)



**Portable Transmitter
TE-100 Series**

- TE-100NA : For Tone only pager application
- TE-100RA : For Alpha pager application, 30 alpha canned message
- TE-100RN : For Numeric pager application, 20 digit numeric message
- Up to 100 capcodes, USB port for serial data and prograing
- Active Voltage Range: 3 Ni-MH battery



**Amplifier
TA-500**

- 430~470MHz
- POCSAG Transmitter
- Input 0.5~1 W, up to 5 Watt



LRCM-R

- 4/8 Relays
- DC coil 530 mW
- Ambient temp 70°C
- Contact rating: 24VDC, 16A / 250VAC



AES Box

- Encrypted 128 bit
- Power supply DC5V
- RS232 port to PC



**POCSAG Receiver
RX-100 Series**

- Extending coverage with max. 32 units
- Distance between each unit up to 400 meters
- RSSI (Received Signal Strength Indicator)
- AES Decryption, Relay Output (Option)



**Tone only transmitter
TE-300**

- Support 50 pagers
- RS232 serial port
- Compatible with Tone only pager



TE-310

- One touch Staff Call transmitter
- Up to 19 pagers
- Each with it's own canned message



**Portable Transmitter Series
TE-100U**

- 1, 4, 8 buttons provide multiple messaging capability
- Message: Max. 640 letters
- USB charging and programming
- Multi-Protocol including COMP1, COMP2, SCOPE, TAP Protocol, GACOMP2, ESPA Protocol 4.4.4



**Transmitter
TX-200**

- AES encryption
- TCP/IP, Alarm input
- Frequency adjusting knob, Support Multiple Protocols



**Repeater
RP-125**

- Repeat Pocsag Signal
- Output power up to 5W
- RS232 port



**Waiter Call
System**

- UHF band
- Waterproof-IP67
- Support 50 pcs table caller (Optional)
- Coverage can reach to 400-meter



**Nurse Call
System**

- Doctor, Nurse Button
- TX Frequency: 433.92
- A panel indicator with 50 backlit LED buttons



**Personal Caring System
JD-100T**

- The Transmitter is waterproof and suitable for wearing even in a shower or for use in other wet environments such as hospitals, bathroom etc.
- battery life (20 times per day 1 year)
- The coverage can reach up to 0.8-1 KM in open space, while it's about 200-300 meters indoor



JD-170

Scan QR code for more information





The great varieties we offer are :

- System solutions for hospitality, hospital, caring center or on-site paging.
- Wireless transmitter and receiver. Receivers with various types such as Tone only, Numeric, Alphanumeric, Voice pager or LED displays. IP standard are available. Transmitter with frequency (VHF) 138-174 MHz, (UHF) 430-470 MHz and 868.25 MHz. Output power in wide range 10mW to 5W.
- Wireless data-transmitting or wireless control usage.



WWW . G A P O L L O . C O M . T W

 886-2-2698-8888

 886-2-2698-1750

gapollo@gapollo.com.tw